



SEALED CHAMBER GAS WATER HEATER DUAL



High DHW output



No pilot flame



Multifunctional touch display



Closed chamber



Gas and temperature sensor



Multiple protection



Gas pipeline (C12, C32)



Class 6 NOx

MODEL				
EAN CODE				
	GIA-CLE-11NOXDUGN	GIA-CLE-11NOXDUGLP	GIA-CLE-11NOXDUGN*	GIA-CLE-11NOXDUGLP*
	8435483848788	8435483848771	8435483830882	8435483830899
Power supply	220-240V (1 Phase ~ 50Hz)			
	POWER			
Input power	kW	22	22	22
Useful power	kW	19,2	19,2	19,4
Min. Input power	kW	9,5	9,5	10,8
Min. Output power	kW	8,2	7	9,5
Performance	%	77,24	77,24	85
Declared Profile	—	M	M	M
Energy classification	—	A	A	A
	PERFORMANCE			
Gas type	—	Natural G20	Butane G30 / Propane G31	Natural G20
Combustion	—	Closed chamber	Closed chamber	Closed chamber
Gas pressure	mbar	20	28 - 30 / 37	20
Maximum gas consumption	m³/h	2,36	0,68/0,89	2,36
NOx emission	mg/kWh	38,13	54,5	27
	FEATURES			
Maximum pressure	bar	10	10	10
Minimum pressure	bar	0,2	0,2	0,2
Flow rate (2BAR)	L/min	11	11	11
Minimum flow (2BAR)	L/min	8	8	8
Water temperature	°C	35 ~ 65	35 ~ 65	30 ~ 60
Sound level	dB	60	60	60
	DIMENSIONS AND WEIGHT			
Net dimensions (W × H × D)	mm	372×663×223	372×663×223	370×660×213
Gross dimensions (W × H × D)	mm	435×800×280	435×800×280	435×800×280
Net weight	kg	12,25	12,25	14,5
Gross weight	kg	13,85	13,85	16,4
	CONNECTIONS			
Gas connection	in.	1/2"	1/2"	1/2"
Cold water connection	in.	1/2"	1/2"	1/2"
Hot water connection	in.	1/2"	1/2"	1/2"
Ø Gas outlet	mm	Ø60/100	Ø60/100	Ø60/100
Max. gas outlet length	m	4	4	4

*Until end of stock