



LOW NOX SEALED
GAS HEATER

ROMBO



Class 6 NOx



SHW big production



No pilot flame



Super slim



Compatible with solar energy



Oxygen free copper exchanger



Gas outlet kit (C13, C33)

MODEL	GIA-CLE-12NOXROGN		GIA-CLE-12NOXROGLP	
EAN CODE	8435483817548		8435483817555	
Power supply	V,F,Hz	220-240V (1 Phase~ 50Hz)		
POWER				
Input power	kW	24	24	
Useful power	kW	21,1	21,1	
Input power	kW	7	7	
Power output	kW	6,4	6,4	
performance	%	78	78	
Declared Profile	—	M	M	
Energy classification	—	A	A	
PERFORMANCE				
Gas type	—	Natural Gas G20	Butane Gas G30 / Propane G31	
Combustion	—	Closed chamber	Closed chamber	
Gas pressure	mbar	20	28 - 30 / 37	
Maximum gas consumption	m³/h	2,54	0,74	
NOx emission	mg/kWh	40	50	
FEATURES				
Maximum pressure	bar	10	10	
Minimum pressure	bar	0,2	0,2	
Flow rate (2BAR)	L/min	12	12	
Minimum flow (2BAR)	L/min	8	8	
Water temperature	C°	35 ~ 65	35~65	
Sound level	dB	61	61	
DIMENSIONS AND WEIGHT				
Net dimensions (W × H × D)	mm	345×570×150	345×570×150	
Gross dimensions (W × H × D)	mm	430x760x250	430x760x250	
Net weight	kg	12,3	12,3	
Gross weight	kg	15,4	15,4	
CONNECTIONS				
Gas connection	in.	1/2"	1/2"	
Cold water connection	in.	1/2"	1/2"	
Hot water connection	in.	1/2"	1/2"	
Ø Gas outlet	mm	Ø 60/100	Ø 60/100	
Max. gas outlet length	m	3	3	