

HOME RANGE | SPLIT 1x1

AROMA 2E

3 YEARS
WARRANTY
TOTAL
QUALITY COMMITMENT

10 YEARS
WARRANTY
COMPRESSOR
QUALITY COMMITMENT

21dB
DEPENDENT ON MODEL

A++
SEER

A+
SCOP

A+++
SCOP
Warmer



Enjoy the comfort

With the Aroma 2E split you will be able to live the best comfort, with its triple filter you will eliminate bad odors and small particles, also thanks to its included Wi-Fi you will be able to control all the functions wherever you are.

**TRIPLE
FILTER**

SERIE AROMA
giatsu
RELIABILITY
SINCE 2017



Clean Air

Includes Cold Catalyst, Silver Ion and Activated Carbon filters to eliminate bad odors and particles.




Wifi Included

You can control the equipment from a smartphone, tablet or by voice with Alexa and Google Home.

CONECTA+

Optional Conecta+

Special plate for automatic ON/OFF switching of the air conditioning in hotel cards, tourist flats or window sensors.



Versatility

Supports long installation distances: 50 m distance and 25 m drop (for 7.1 kW model).



Service life

The coils of the indoor and outdoor unit have Golden Fin protection, an anticorrosive for saline environments that extends their durability.



Comfort

With the "I Feel" function, the split takes as the reference temperature of the room the one with the remote control.



Efficient

Energy classification A++ in cooling and A+++ in heating for hot areas.



**TRIPLE
FILTER**

SPLIT 1X1
AROMA 2E

CONNECTA+
Optional



MODELS		INT.	GIA-S09AR2E-R32 GIA-S09AR2E-R32-I GIA-S09AR2E-R32-O	GIA-S12AR2E-R32 GIA-S12AR2E-R32-I GIA-S12AR2E-R32-O	GIA-S18AR2E-R32 GIA-S18AR2E-R32-I GIA-S18AR2E-R32-O	GIA-S24AR2E-R32 GIA-S24AR2E-R32-I GIA-S24AR2E-R32-O
EAN CODE		EXT.	8435483854017	8435483853980	8435483854413	8435483854444
Electrical power supply		V,F,Hz	220-240V (1 Phase ~ 50Hz) / Outdoor unit			
PERFORMANCE						
Cooling capacity	Capacity	kW	2,64 (1,00-3,40)	3,5 (1,11-3,92)	5,28 (1,99-6,73)	7,03 (2,08-7,92)
		Btu/h	9.000 (3.100-11.600)	12.000 (3.800-13.400)	18.100 (6.800-2.300)	23.900 (7.100-27.000)
	Consumption	W	800(100-1240)	1320(83-1600)	1550 (140-2300)	2600 (420-3150)
	Current	A	3,48	5,8	6,7	11,5
	SEER	W/W	7	6,5	7,4	6,1
	Energy class	Cold	A++	A++	A++	A++
	Annual consumption	kWh	130	188	247	405
Heating capacity	Capacity	kW	2,93 (0,84-3,37)	3,81 (1,09-4,17)	5,57 (1,29-6,74)	7,33 (1,62-7,92)
		Btu/h	10.000 (2.800-11.500)	13.000 (3.700-14.200)	18.800 (4.400-23.000)	24.900 (5.500-27.000)
	Consumption	W	930 (120-1.200)	1.190 (167-1.400)	1.570 (220-2350)	2.400 (300-2.750)
	Current	A	4,05	5,3	6,8	11
	SCOP	W/W	4,1	4,1	4,0	4,0
	Energy class	Heat	A+	A+	A+	A+
	Annual consumption	kWh	792	957	1435	1680
FEATURES						
Indoor unit	Sound power (H/M/L/S)	dB	50	54	56	59
	Sound pressure (H/M/L/S)	dB	37/32/25/21,5	39,5/35,5/25/21,5	42,5/36/26/20	45/40,5/36/29,5
	Air flow (H/M/L/S)	m³/h	435/333/259	530/430/310	840/680/540	980/817/662
	Temperature range	°C	17-32/0-30	17-32/0-30	17-32/0-30	17-32/0-30
Outdoor unit	Sound power	dB	59	64	63	67
	Sound pressure	dB	55	55	56	59
	Air flow	m³/h	1750	1750	2100	3500
	Operating temperature	°C	-15-50/-20-30	-15-50/-20-30	-15-50/-20-30	-15-50/-20-30
Refrigerant	Compressor	Type	ROTARY	ROTARY	Rotary	Twin-rotary
		Brand	GMCC	GMCC	GMCC	GMCC
	Type/Charge	R32/kg	0,47	0,52	1,08	1,42
	Carga adicional	g/m	12	12	12	24
DIMENSIONS AND WEIGHT						
Indoor unit	Net dimensions (W×H×D)	mm	715x194x285	805x194x285	957x302x213	1040x327x220
	Gross dimensions (W×H×D)	mm	780x270x365	870x270x365	1035x385x295	1120x405x315
	Net/Gross weight	kg	6,7/8,8	7,3/9,5	10/13	12,3/15,8
Outdoor unit	Net dimensions (W×H×D)	mm	720x270x495	720x270x495	805x554x330	890x673x342
	Gross dimensions (W×H×D)	mm	835x300x540	835x300x540	915x615x370	995x740x398
	Net/Gross weight	kg	21/22,8	21/22,8	32,7/35,4	42,9/45,9
CONNECTIONS						
Refrigeration pipe	Liquid – Gas	in.	1/4-3/8	1/4-3/8	1/4-1/2	3/8-5/8
	Max. length	m	25	25	30	50
	Max. elevation	m	10	10	20	25
Electric connections	Power supply	mm	2x2,5+T	2x2,5+T	2x2,5+T	2x2,5+T
	Interconnection	mm	4x2,5+T	4x2,5+T	4x2,5+T	4x2,5+T

Notes:

Capacity data in standard conditions. Actual data will vary depending on where the equipment is installed and how it is used.
The dimensions of the electrical wiring are approximate, they should be calculated according to the conditions of the installation itself.